ChemMax® 1 Boot Cover

C1T905

Product features

- ChemMAX1 fabric with double layer anti-slip sole.
- Elasticated ankle and top.
- Taped seams for superior protection and strength.
- Infectious Agent Barrier - passes at highest classes in all four EN 14126 bio-hazard tests.

Application

- General industry, environmental clean up and chemical handling.
- Taped seams for additional protection from liquid splash.

Fabric physical property

Physical Property	Test Method	Test Result
Basis Weight	ISO 3801:1997	87g/m²
Abrasion Resistance (No of cycles)	EN530:1994 method 2	100-500
Flex Cracking Resistance	EN ISO7854:1997 method B	1000-2500
Tensile Strength (MD/CD)	EN ISO 13934-1:1999	120N/73N
Tear Resistance (MD/CD)	ISO9073-4:1997	81.5N/43.6N
Puncture Resistance	EN863:1995	13N
Burst Strength	ISO13938-1:1999,50cm²	63.7KPa
Seam Strength	EN ISO 13935-2:1999	170N
Electrostatic properties	EN1149-1:2006/EN1149-5:2008	Pass

Product style	Color	Seam Method	Sizes	Case Pack
C1T905	Yellow	Heat sealed seam	One size	100

Lakeland
Protect Your People™

Lakeland Asia Pacific
Unit 503, Building B, Sinolight Plaza, No.4 Wangjing Qiyang Road,
Chaoyang District, Beijing 100102, P.R. China
Tel: (+86) 10 64379226 Fax: (+86) 10 64379918
Email: sales-ap@lakeland.com
Web: www.lakeland.com